



## SPÉCIFICATIONS TECHNIQUES

# RENTAL DUAL

Pixel Pitch (mm)	1,9 mm	2.6 mm	3.9 mm	4.8 mm
Type de pixel	SMD1515	SMD1515	SMD2121	SMD2121
Densité de pixels	270.000 px / m <sup>2</sup>	147.456 px / m <sup>2</sup>	65.536 px / m <sup>2</sup>	43.264 px / m <sup>2</sup>
Luminosité (cd/m <sup>2</sup> )	800 nits	1000 nits	1000 nits	1000 nits
Fréquence de rafraîchissement (Hz)	3840 Hz Confi.	3840 Hz Confi.	3840 Hz Confi.	3840 Hz Confi.
Résolution des modules	128 x 128 px	96 x 96 px	64 x 64 px	52 x 52 px
Dimensions des modules	250 x 250 mm	250 x 250 mm	250 x 250 mm	250 x 250 mm
Résolution du Cabinet	256 x 256 px	192 x 192 px	128 x 128 px	104 x 104 px
Dimension de l'armoire	500x500mm	500x500mm1000x500mm	500x500mm1000x500mm	500x500mm1000x500mm
Poids de l'armoire	5.5 kg	5.5 / 9 Kg	5.5 / 9 Kg	5.5 / 9 Kg
Épaisseur de l'armoire	53.5 mm	53.5 mm	53.5 mm	53.5 mm
Consommation Max. (Watt)	180W Cabinet	180W Cabinet	420 W Cabinet	420 W Cabinet
Consommation moyenne (Watt)	70W Cabinet	70W Cabinet	130 W Cabinet	130 W Cabinet
Angle de vision	160°/140°	160°/140°	160°/140°	160°/140°
Protection	IP-20	IP-20	IP-20	IP-20
Entrée de puissance	100 - 240V AC 50-60	100 - 240V AC 50-60	100 - 240V AC 50-60	100 - 240V AC 50-60
Température de fonctionnement	-20 - +45	-20 - +45	-20 - +45	-20 - +45

